

SABIC JAPAN L L C
PACIFIC GRADES - RESIN
2-2 KINUGAOKA
MOKA-SHI TOCHIGI-KEN 321-4392 JP

CY5000(GG)

Polycarbonate/Acrylonitrile Butadiene Styrene (PC/ABS) "Cycoloy", furnished as pellets
(GG): Denotes a global grade formulation previously in File E161759.

NOTE: Material designation may be followed by a color nomenclature consisting of either an alpha/numeric or numeric/alpha combination.

Flammability	Value	Test Method
Flame Rating		
1.5 mm	V-1 (ALL)	IEC 60695-11-10
2.0 mm	V-0 (ALL)	IEC 60695-11-10
3.0 mm	V-0 (ALL)	IEC 60695-11-10
Thermal	Value	Test Method
RTI Imp		
1.5 mm	60 °C	UL 746B
2.0 mm	60 °C	UL 746B
3.0 mm	60 °C	UL 746B
RTI Str		
1.5 mm	60 °C	UL 746B
2.0 mm	60 °C	UL 746B
3.0 mm	60 °C	UL 746B
RTI Elec		
1.5 mm	60 °C	UL 746B
2.0 mm	60 °C	UL 746B
3.0 mm	60 °C	UL 746B



Go To UL iQ Link (<https://iq.ul.com/ul/cert.aspx?ULID=574964>)

Report Date: 2000-02-11
Last Revised: 2016-11-14

此数据表中的信息由塑库网 (<https://www.plasdata.com>) 从该材料的生产商处获得。塑库网尽最大努力确保此数据的准确性。但是塑库网对这些数据值不承担任何责任，并强烈建议在最终选择材料前，就数据值与材料供应商进行验证。